



# Futrol Petrochem

A chemistry of trust. Since 2001

## TECHNICAL DATA SHEET

HEAVY NAPHTHA			
ANALYSIS	UNIT	LIMIT	TEST METHOD
Density @15.0 °C	Kg/m 3	0.7580 Max	ASTMD1298
Distillation	°C		ASTM D86
10 % Evaporated Temp	°C	120 Max	ASTM D86
50 % Evaporated Temp	°C	115 Min	ASTM D86
95 % Evaporated Temp	°C	150-170	ASTM D86
F.B.P	°C	180 Max	ASTM D86
Residue	%Vol	1.5 Max	ASTM D86
Loss	%Vol	1 Max	ASTM D86
Total Sulphur	%wt	0.08 Max	ASTM D1266
Corrosion 3HRS	50 °C	No 1 strip	ASTM D130
Vapor Pressure	K.pa	27 Max	ASTM D323
Mercaptan Content	ppm	70 Min	ASTM D3227
Colour, Saybolt	-	25 Min	ASTM D156
Paraffins Content	%Vol	50 Min	ASTM D1319
Oleffins Content	%Vol	1.5 Max	ASTM D1319
( Naphthens +Aromatics ) Content	%Vol	40 Min	ASTM D1319
Lead (PB) P.P.B	UOP	40 Max	350 -68T
C/H Ratio	Estimated	6 Max	Calculate
Gum Existent (air jet)	Mg/100ml	2.5 Max	ASTM D381
Oxygenates	ppm	60 Max	ASTM D4815

For more information about this product and other products in our range please scan the following

WEBSITE  
[www.futrolpetrochem.com](http://www.futrolpetrochem.com)

EMAIL SALES  
[sales@futrolpetrochem.com](mailto:sales@futrolpetrochem.com)