



Futrol Petrochem

A chemistry of trust. Since 2001



TECHNICAL DATA SHEET

| SPECIFICATION OF LOW AROMATIC WHITE SPIRIT (LAWS) HIGH FBP | | | |
|--|-------------------|--------------|-------------|
| CHARACTERISTICS | UNITS | REULT | TEST METHOD |
| Density | Kg/m ³ | 0.79-0.8 min | ASTM D 1298 |
| Distillation | --- | --- | ASTM D 86 |
| I.B.P | °C | 142 - 158 | ASTM D 86 |
| F.B.P | °C | 210 - 230 | ASTM D 86 |
| 10% Evaporated | °C | 158 min | ASTM D 86 |
| 60% Evaporated | °C | 198 max | ASTM D 86 |
| 90% Evaporated | °C | 230 max | ASTM D 86 |
| Residue | Vol% | 1.5 max | ASTM D 86 |
| Color Say Bolt | --- | 30 min | ASTM D 156 |
| Odor | --- | Merchantable | --- |
| Flash Point | °C | 38 min | ASTM D 56 |
| Corrosion -3hr @ 100°C | --- | 10 | ASTM D 130 |
| Sulphur Total | ppm | 800 min | ASTM D 4294 |
| Doctor Test | --- | Negative | ASTM D 4952 |
| Aromatic Content | Vol% | 20 max | ASTM D 1319 |
| Gum Existent | Mg/100ml | 5 max | ASTM D 381 |
| Neutrality | --- | Pass | ASTM BS 245 |
| Acidity of Residue | --- | Pass | ASTM D 1093 |

For more information about this product and other products in our range please scan the following

WEBSITE
www.futrolpetrochem.com

EMAIL SALES
sales@futrolpetrochem.com