



Futrol Petrochem

A chemistry of trust. Since 2001



TECHNICAL DATA SHEET

LIGHT NAPHTHA			
ANALYSIS	UNIT	LIMIT	TEST METHOD
Density	Kg/m3	700 max	ASTM D 1298
Distillation	°C		ASTM D 86
I.B.P	°C	35 min	ASTM D 86
10% Evaporated Temp	°C	60 max	ASTM D 86
50% Evaporated Temp	°C	85 min	ASTM D 86
95% Evaporated Temp	°C	125 max	ASTM D 86
F.B.P	°C	150 max	ASTM D 86
Residue	Vol%	1.5 max	ASTM D 86
Loss	Vol%	1 max	ASTM D 86
Total Sulphur	%wt	0.03 max	ASTM D1266
Corrosion -3 HRS	50°C	No 1 strip	ASTM D 13
Vapour Pressure	K.Pa	75 max	ASTM D 32
Mercaptan Content	Ppm	25 max	ASTM D 4322
Color ,say bolt	--	2 min	ASTM D 156
Paraffins Content	Vol%	70 min	ASTM D 131
Olefins Content	Vol%	2 max	ASTM D 131
Naphthenes Content	Vol%	10 min	ASTM D 131
Aromatic Content	Vol%	5 min	ASTM D 131
Lead (PB)P.P.B	Uop	40 max	350-68T
C/H Ratio	Estimated	5.5 max	Calculate
Gum Existent (air jet)	Mg/100ml	3 max	ASTM D 381

For more information about this product and other products in our range please scan the following

WEBSITE
www.futrolpetrochem.com

EMAIL SALES
sales@futrolpetrochem.com