



# Futrol Petrochem

A chemistry of trust. Since 2001



## TECHNICAL DATA SHEET

SPECIFICATION OF MIX XYLENE			
		VALUE	
	ASTM D-4052	TO BE REPORTED	gr/cm3
		Velar free of	
Appearance	Visual	Haze/sediment	
Color Pt-Co Scale	ASTM D-1209	10 max	
Acid Wash Color	ASTM D-848	6 max	
Acidity	ASTM D-847	No free acid	mrg NaOH/100ml
Copper Corrosion	ASTM D-849	No.1a	
H2S % S02 Content	ASTM D-853	Free of H2S/S02	
	ASTM D-850	5 max	
I.B.P	ASTM D-850	137 min	
D.P	ASTM D-850	143 max	
Para-Xylene	ASTM D-2306	16.5 min	Wt.%
Ortho-Xylene	ASTM D-2306	15 min	Wt.%
Ethyl Benzene	ASTM D-2306	18.5 max	Wt.%
Metha Xylene	ASTM D-2306	49 max	Wt.%
Benzene	ASTM D-2306	0.005 max	Wt.%
Toluene	ASTM D-2306	0.4 max	Wt.%
C9 Aromatics	ASTM D-2306	0.5 max	Wt.%
	ASTM D-2306	0.05 max	Wt.%
Total Sulfur	UOP 727	1 max	Wt.ppm
Total Chlorides	IP-AK/81	1 max	Wt.ppm
Bromine Index	IP-129	20 max	mrg/100 gr

For more information about this product and other products in our range please scan the following

WEBSITE  
[www.futrolpetrochem.com](http://www.futrolpetrochem.com)

EMAIL SALES  
[sales@futrolpetrochem.com](mailto:sales@futrolpetrochem.com)