



Futrol Petrochem

A chemistry of trust. Since 2001



TECHNICAL DATA SHEET

SPECIFICATION OF RAFFINATE II			
TYPICAL TEST	UNIT	SPECIFICATION	TEST METHOD
RVP	Psia	Max 9.5	ASTM D-86
IBP	°C	32-52	ASTM D-86
10%	°C	53-63	ASTM D-86
50%	°C	64-78	ASTM D-86
90%	°C	87-100	ASTM D-86
FAB	°C	101-130	ASTM D-86
Total Recovery	%	Min 97	ASTM D-86
Paraffins	Wt%	Max 92	IFP 9302
Olefins	Wt%	Max 5	IFP 9302
Naphthenics	Wt%	4.5-10	IFP 9302
Aromatics	Wt%	Max 6	IFP 9302
Density @ 15.6 °C	Gr/cm3	0.65-0.7	ASTM D 4052
Total Sulfur	Ppm	Max 5	ASTM D-4553
color	-	15 max	ASTM D-1209

LPG SPECIFICATION			
TYPICAL TEST	UNIT	SPECIFICATION	TEST METHOD
C6+	Wt %	Max 2%	ISO 7941

For more information about this product and other products in our range please scan the following

WEBSITE
www.futrolpetrochem.com

EMAIL SALES
sales@futrolpetrochem.com