

The international codes will be strictly enforced
 Exclude all intruders that send out false information.
 Those who submit a false, LOI, ICPO, RWA or PI and SCO
 WILL BE CHARGED WITH A CRIME



Royal Global Energy

Telephone: + 98 21 8822 7734
 + 98 21 8822 7735

Fax: + 98 21 8822 7736

Mob: +98 912 450 21 90 Eng. Behrooz Mirzaei

Email: info@royalglobalenergy.com

No: 1401 2th floor, Noor Tehran Building, Valiasr Ave, Tehran, Iran

RGE main core business Oil, Gas, Refining and Petrochemicals

Sulfur Granular

TEST	RESULT
PURITY (ON DRY BASIS) (WT %) MIN.	99.50
ASH CONTENT (WT %) MAX.	0.05
MOISTURE (WT %) MAX.	0.50
ORGANIC (WT %) MAX.	0.05
ACIDITY (WT %) MAX.	0.02
COLOR	BRIGHT YELLOW
FORM	GRANULAR
PORT RESTRICTIONS	
LOAD RATE: 5000 MT PER WEATHER WORKING DAY	
MIN QUANTITY :15,000 MT	
JETTY RESTRICTION:	
L.O.A=780 FT(237.5M) BEAM:NO LIMITATION DRAFT:MAX 11.50 M	