



Futrol Petrochem

A chemistry of trust. Since 2001



TECHNICAL DATA SHEET

SPECIFICATION OF FUEL OIL 380 AND 180						
TEST	UNIT	ASTM METHOD	IFO 380		IFO 180	
			MINIMUM	MAXIMUM	MINIMUM	MAXIMUM
Density at15 °C	Kg/m ³	ASTMD D-129		991		991
Kinematic Viscosity	cSt	ASTMD D-445		380		180
Flash Point	°C	ASTMD D-93	60		60	
Pour Point	°C	ASTMD D-97		10		30
Carbon Residue	%m	ASTMD D-4530		18		20
Ash	%m	ASTMD D-482		0.15		0.15
Water	%	ASTMD D-95		1		1
Sulfur	%m	ASTMD D-4294		3.5		3.0
Vanadium	mg/kg	ASTMD D-1548		300		500
Aluminum and Silicon	mg/kg	ASTMD D-5184		80		80
Total Sediment	%m	ASTMD D-4870		0.1		0.1
Acid Number	mgKOH/g	ASTMD D-664		3		3
CCAI				860		860

For more information about this product and other products in our range please scan the following

WEBSITE
www.futrolpetrochem.com

EMAIL SALES
sales@futrolpetrochem.com