



Futrol Petrochem

A chemistry of trust. Since 2001



TECHNICAL DATA SHEET

GASOIL 500 PPM			
ANALYSIS	UNIT	LIMIT	TEST METHOD
Density @ 15 °C	Kg/m3	820-860	ASTM D 1298
Distillation: Recovered @150 °C Recovered @300 °C Recovered @357 °C	Vol %	Report	ASTM D86
	Vol %	report	ASTM D86
	Vol %	90 min	ASTM D86
F.B.P	°C	385 max	ASTM D86
Color	-	3 max	ASTM D1500
Flash point	°C	54 min	ASTM D93
Sulphur Total	Wt%	0.05 max	ASTM D1552
Corrosion-3 h rs @ 100 °C	-	Ia	ASTM D130
Viscosity Kinematic @37.8 °C	c.St	2.0-5.5	ASTM D445
Cloud point	°C	*2.0 max	ASTM D2500
Pour point	°C	*-3.0 max	ASTM D97
Carbon Residue {on 10% Bottoms}	wt%	0.1 max	ASTM D189
Ash	wt%	0.01 max	ASTM D482
Water & Sediment	Vol%	0.05 max	ASTM D2709
Cetane Index	-	49 min	ASTM D976

For more information about this product and other products in our range please scan the following

WEBSITE
www.futrolpetrochem.com

EMAIL SALES
sales@futrolpetrochem.com